

SPECIFICATIONS

Current rating : 3 Amp . Max ..

Dielectric Withstanding Voltage : 1000V AC RMS for 60Seconds

Contact resistance : 30m Ohms Max.

Insulation resistance : 1000M Ohms Min . At 1000V DC .

Temperature range : - 55°C ~ + 105°C

Housing : Thermoplastic(UL94V-0),Black

Terminal : Copper Alloy(t=0.40mm),Gold Plating


ORDER INFORMATION:





HFDR1 - XX 6 - X0 - X - XX - X
 a b c d e f g


- a. Pin of numbers: b. Pastic Thick :
 04 ~ 80 6: 5.7mm
- c. Plated selection:
 0 : Tin plated
 1 : Gold flash
 2 : 3u" Gold on Contact Area
 3 : 5u" Gold on Contact Area
 4 : 10u" Gold on Contact Area
 5 : 15u" Gold on Contact Area
 6 : 20u" Gold on Contact Area
 7 : 30u" Gold on Contact Area
- d. Solder Pin length :
 1 : L=3.1mm
- e. Plastic Color :
 B : black color
- f. Plastic material selection:
 P : P.B.T (off料)
 E : P.B.T (新料)
 N: Nylon6T
- g. Pack selection:
 C : Contron Pack D : Disk Pack
 T : Tube Pack
 R : Reel Pack.

VERSION & EC DESCRIPTION

DATE	VERSION	PAGE	DESCRIPTION
2005/03/31	A	24-25	Add HFDR1-XX5 Plan

GENAL TOLERANCE X. ± .X ± 0.30 .XX ± 0.20 .XXX ± 0.10	DRAW DATE 2005/03/31 H. D. LI	PART NO HFDR1-XX6-X0-X-XX-X
	DESIGN H. D. LI	TITLE 2.54 母座 H=5.7 Right Angle Type Dual Rows
	CHECKED Y. M. LU	
UNIT :mm	APPROVED J. F. KANG	 宏揚精密有限公司 HOJAR PRECISION CO., LTD.



GENERAL TOLERANCE X. ± .XX ± 0.30 .XXX ± 0.20 .XXX ± 0.10	DRAW DATE	2005/03/31 H. D. LI	PART NO HFDR1-XX6-X0-X-XX-X
	DESIGN	H. D. LI	
	CHECKED	Y. M. LU	2.54 母座 H=5.7 Right Angle Type Dual Rows
	APPROVED	J. F. KANG	 宏揚精密有限公司 HOJAR PRECISION CO., LTD.
UNIT :mm			