



Material:
NORYL94V1-SE100V



Poles	Dimension (mm)		Poles	Dimension (mm)	
	B	A		B	A
1		2.65	21	50.80	53.54
2	2.54	5.28	22	53.34	56.08
3	5.08	7.82	23	55.88	58.62
4	7.62	10.36	24	58.42	61.16
5	10.16	12.90	25	60.96	63.70
6	12.70	15.44	26	63.50	66.24
7	15.24	17.98	27	66.04	68.78
8	17.78	20.52	28	68.58	71.32
9	20.32	23.06	29	71.12	73.86
10	22.86	25.60	30	73.66	76.40
11	25.40	28.14	31	76.20	78.94
12	27.94	30.68	32	78.74	81.48
13	30.48	33.22	33	81.28	84.02
14	33.02	35.76	34	83.82	86.56
15	35.56	38.30	35	86.36	89.10
16	38.10	40.84	36	88.90	91.64
17	40.64	43.38	37	91.44	94.18
18	43.18	45.92	38	93.98	96.72
19	40.64	48.46	39	96.52	99.26
20	43.18	51.00	40	99.06	101.8

註: A,B尺寸公差:

- 1*2P~1*10P ±0.20
- 1*11P~1*20P ±0.25
- 1*21P~1*30P ±0.35
- 1*31P~1*40P ±0.45
- 1*41P~1*50P ±0.50

GENAL TOLERANCE ± ± ±	DATE H. D. LI	PART NO HS254- XX2
	DESIGN H. D. LI	TITLE 杜邦2.54mm Housing 單排
	CHECKED Y. M. LU	
UNIT :mm	APPROVED J. F. KANG	 宏揚精密有限公司 HOJAR PRECISION CO., LTD.